

Seven fat years or seven lean years for freight transport modelling? Developments since 2013

Gerard de Jong – ITS Leeds and Significance

Michiel de Bok – Delft University of Technology and Significance

Sebastiaan Thoen – Significance

Abstract

Freight transport modelling has seen many developments in this century. A key trend was the inclusion of more aspects of logistics thinking in freight transport models for the public sector. In de Jong et al. (2013) is a list of topics that were expected to be the main areas for further development in freight transport modelling in the next decade. The current paper describes the developments that have actually taken place in modelling freight transport, at the international, national, regional and urban level, and compares these to the list in the 2013 paper.

Keywords: Freight transport model, transport logistics, transport chain, deliveries, city logistics

1. Introduction

For a long time freight transport modelling was an under-researched topic and most of the applications to freight transport borrowed heavily from passenger transport modelling. Only occasionally innovative work took place. This includes Bayliss (1988) and especially Bayliss and Edwards (1970) that already had a probability model at the level of individual consignments. Other examples of early innovative papers in freight transport modelling are Baumol and Vinod (1970), that combined transport and inventory considerations, and the applications of random utility modelling (albeit transferred from passenger transport) in Chiang et al. (1981) and Winston (1981). Since the start of the new millennium, freight transport modelling has been receiving much more attention and seen more development.

A paper published in 2013 (de Jong et al., 2013) reviewed the freight transport models that were available at the time, with a focus on the national and international level and on Europe. It concluded that in the decade up to 2013 the main development in the freight transport models at these levels was the inclusion of more logistics components (such as inventory considerations and use of multimodal transport chains, consolidation and distribution instead of a single main mode). This paper also included a list of key developments that were expected to take place in freight transport modelling in the years to come. Even though some of these developments had already begun, predictions of which new topics will be studied and which new methods developed are highly uncertain. The actual developments in freight transport modelling depend on many different researchers with their own research interests and skills, and also on the topics that are debated in transport policy making, which may shift over time.

The key developments expected for the next decade mentioned under ‘The road ahead’ in de Jong et al. (2013) were:

- Integration of production, inventory and transport logistics;
- Modelling of further logistics decisions, especially supply chain formation;
- Departure time modelling;
- Integration of (inter)national (intercity) freight models with urban freight models;
- Integration of freight transport models with passenger transport models;

- Including latent variables (e.g. on attitudes) in freight transport models leading to hybrid models with hard (e.g. time and cost) and soft (e.g. attitude towards the environment) variables.

The current article will review developments in applied freight transport modelling since the 2013 paper, that is during the previous seven years. Unlike the 2013 paper, we will also discuss urban freight transport models, since many of the development in recent years have occurred in freight models at this level. We also include developments that have taken place outside Europe. Similar to the 2013 paper, we will not discuss models used in the private sector to optimise a firm's transport activities, but restrict ourselves to freight transport models developed for transport authorities or to study freight transport in some geographic study area in academia.

In section 2 the paper will first review international freight transport models, followed by sections 3, 4 and 5 on national, regional and urban models respectively. Then in section 6, we will take each of the expected developments from de Jong et al., 2013 and discuss whether the expected changes have actually taken place. Section 7 will look at other important developments in freight transport modelling, that were not foreseen in the list of 2013, but that can be observed to be happening. A summary and conclusions on whether the past seven years have been fat or lean for freight transport modelling, and also including a future outlook, will be provided in section 8.

2. Developments in international freight transport models

Most of the freight transport models at the European level that were mentioned in de Jong et al. (2013) have been superseded by newer models. More recently developed models that operate at the European level are HIGH-TOOL, Transtools3, TRUST and TRIMODE. All these models include both passenger and freight transport. Below, we briefly discuss each of these.

HIGH-TOOL (Szimba et al., 2018) is a strategic transport policy assessment instrument, developed for the European Commission. It is relatively easy and fast to use and is open-source, so as to allow policymakers to apply the model for themselves to strategically evaluate the impacts of transport policies on transport, environment and economy. The model is broad (also includes an Economy and Resources module following spatial computable general equilibrium (SCGE) principles, vehicle stock models, demography, the environment and safety), but to remain fast had to compromise on spatial detail (it uses 314 zones, corresponding to NUTS2 in the EU and coarser outside) and network assignment was excluded.

The freight transport model within HIGH-TOOL is an aggregate model that follows the conventional four-stage approach in several ways (please note that step four, the network assignment is missing here). However, there are some important aspects where the model goes beyond what is standard in four-stage models:

- The trade projections are produced by the Economy and Resources module and these refer to the flows from the producing zone to the consumption zone of the goods (PC flows, not origin-destination OD flows that are used in most conventional freight models). There are several advantages of a PC-based approach for modelling trade over an OD-based approach (Ben-Akiva and de Jong, 2013). In a PC-based model, the forecasts of the trade flows will be based on economic development in the producing and consuming regions, not on what happens in intermediate regions where transshipments take place. However, when it comes to network assignment, OD-flows are the relevant measure. In practice, many transports go through transshipment points, and assigning the OD trips within these transport chains is more

accurate. The data available for transport flows (e.g. from traffic counts and interviews with carriers) also are at the OD level.

- The freight transport between the production and consumption zone is modelled by multimodal transport chains, considering the transport modes air, rail, road, inland waterways, and maritime transport. The distribution of mode chains follows a multinomial logit model and distributes the freight flow across multi-modal transport chains (routed through transshipment points) for up to two transshipment points.

The Transtools3 model also follows the distinction between PC flows and OD flows. It differs from other European models in that the central component of its freight transport component, namely the submodel for the choice of (possibly multimodal) transport chains, was estimated on disaggregate data (Jensen et al., 2019). These data sources are the Swedish Commodity Flow Survey 2009 and the French ECHO survey that was carried out in 2004. The modes that can be part of these transport chains are road, rail, inland waterways and sea transport. The transport chain models are nested logit models and different kinds of nonlinear cost functions, including spline functions were tested. The Transtools3 freight model also contains aggregate models for the prediction of the PC flows, with logsums from the chain choice model influencing the trade patterns (de Jong et al., 2017), and for network assignment. Unlike HIGH-TOOL it uses a zoning system that resembles the NUTS3 classification (more than 1500 zones).

TRUST is a network assignment model (TRT, 2018) developed for assessing EU transport policies. It uses a fixed OD matrix for passenger and freight traffic at the NUTS3 level. However, by combining this network module with the older ASTRA passenger and freight transport demand model (that is a system dynamics model), feedback to transport demand can be taken into account to change the OD matrices. TRUST carries out assignments for road, rail and maritime transport.

TRIMODE (Nöckel et al., 2017; Martino et al., 2018) is the latest transport model developed for the European Commission. It comprises passenger and freight transport. Like HIGH-TOOL and Transtools3, the TRIMODE freight transport model also starts from the basic distinction between PC and OD flows. It uses an SCGE Economy model to determine the PC flows, and allows for multimodal transport chains between the production and consumption locations. Unlike Transtools3, the transport chain model is based on aggregate data; this is a nested logit model with main mode, feeder mode and some vehicle type choice. TRIMODE not only models multimodal transport chains but also intermediate storage along the distribution channel, where the storage can take place at national, regional and/or local distribution centres, based on transport and warehousing costs. The spatial level is that of NUTS3, and the modes included for freight transport are: road, rail, inland waterways, maritime, air and pipeline.

Besides freight transport models for Europe, there are also other international models, especially global transport models. In this respect, the WorldNet model that was mentioned in de Jong et al. (2013) is still in use, and there is also a global model, based on transport costs minimisation, for international container transport (Halim, 2017). ITF also has its own transport forecasting tool, that includes a global freight transport model for both domestic and international flows, with components for trade patterns, value-to-weight ratios, mode choice and route choice, all at the aggregate (zonal) level (ITF, 2019). Models that focus on cross-border transport of two countries are discussed under regional models below.

Konstantinus (2019) and Konstantinus et al. (2020) developed a mode choice model for the choice between road transport and short-sea shipping (SSS) for the Southern African Development Community (SADC), an inter-governmental organisation wherein the 16 Southern African countries work together. The model was based on stated preference interviews with shippers and freight forwarders. The models estimated include multinomial and mixed logit, but also latent class models,

where the unobserved heterogeneity between respondents/shipments was linked to characteristics of the product shipped. In this research project, also the integrated choice and latent variable (ICLV) model or 'hybrid model' was employed to assess the attitudes of shippers towards employing SSS.

3. Developments in national freight transport models

BasGoed is the strategic Freight Transport model for the Netherlands. The initial model that was developed almost a decade ago applies the conventional four-step approach, where route choice is handled in already existing individual assignment models for each mode: road, rail and inland waterways (De Jong et al., 2011). Freight generation is modelled in the Economy module that applies economic make/use patterns for the national economy to simulate regional freight demand; international trade scenarios are used to calculate international freight patterns.

The functionality of the BasGoed model was further extended by the implementation of a multimodal transport chain model for container transport (de Bok et al., 2018), that can be used to evaluate the impacts of new multimodal terminals. In the absence of good quality multimodal transport data this model was calibrated by linking unimodal data for different transport modes.

In the latest model improvement stage of BasGoed, the functionality of the Economy Module was improved to be able to include the impact of climate transition on freight transport demand. This transition to a more sustainable energy mix is simulated using a shift functionality that modifies the use of resources in the production function. In addition, the sectoral industry growth scenario, and investment assumptions were modified consistently (Wesseling et al, 2020). Such an application requires specific scenario input on the energy mix, and an input/output growth scenario.

The aggregate-disaggregate-aggregate (ADA) model is a framework for freight transport models at the international, national or regional level, that was originally developed in the first decade of the 20th century (de Jong and Ben-Akiva, 2007; Ben-Akiva and de Jong, 2013). It distinguishes three model steps:

- The PC model that explains trade between the location of production and the location of consumption;
- The logistics model, that explains logistics decisions such as transport chain choice and shipment size choice, and in this way translates the PC flows into mode-specific OD-flows;
- The network model for assignment of origin-destination matrices to the transport networks.

The ADA philosophy is that it is most important that the logistics choices (the 'middle part') are modelled at the level of the individual decision-makers (disaggregate level) because decision-makers on all goods flows between two zones per commodity type do not exist and this would assume a greater level of coordination and optimality than what happens in reality. Modelling the PC flows and the network assignment at the aggregate (zone-to-zone) level on the other hand is acceptable for reasons of data availability and computation time. In order to have a disaggregate logistics model., the outcomes of the PC model have to be allocated to individual firms at both ends (firm-to-firm flows), and before network assignment flows have to be aggregated into OD matrices. The ADA model has been worked out in practice in a number of countries, where gravity models, input-output models or SCGE models are used to obtain the PC matrices, deterministic minimisation of the full logistics costs (including transport, inventory and capital cost) to yield the logistics outcomes at the micro-level and existing commercial packages are used for network assignment. Applications of the ADA model at the national level to date are:

- The Norwegian national freight transport model. This uses the PINGO SCGE model for the generation of PC flows, a deterministic logistics cost minimisation approach and a commercial assignment package.
- The Swedish national freight transport model Samgods, which uses a gravity approach for the PC flows, deterministic logistics cost minimisation and commercial assignment software (also for steering the model as a whole).
- The Danish national freight transport model; this uses a similar approach to the Norwegian and Swedish models (also with deterministic logistic choices), but a special component of the model, the Fehmarn Belt model, that can be run separately, was estimated on disaggregate stated and revealed preference (SP/RP) data.
- Development of an ADA national freight transport model has started in Austria (Grebe et al., 2020). The PC flows will come from an input-output model, the logistics model will be estimated as far as possible on new SP/RP data collected as part of the project and the network assignment and overall model steering will use a commercial package.

The Swedish Commodity flow Survey CFS has been used in several projects to estimate discrete choice models of the choice of transport chain and shipment size in the Swedish freight market (Abate et al. 2014, 2018; Lindgren et al., 2019). The purpose of this set of projects has been to promote the development of a so-called stochastic logistics module in Samgods, where the logistics choices are based on a logit-formula and coefficients are estimated on observed choices by shippers, to replace the currently operational version of Samgods that uses a deterministic logistic costs minimisation for transport chain and shipment size choice. These projects show that estimation of a transport chain and shipment size choice component for a national model system is feasible and leads to more plausible elasticities and forecast in general than a deterministic approach.

The US has also several national freight transport models that have been developed in the recent past, such as the FAME microsimulation model (Samimi et al., 2010), or the nationwide disaggregate mode and shipment size choice models that have been estimated on the US CFS by Holguin-Veras and colleagues at Rensselaer Polytechnic Institute (e.g. Holguin-Veras et al., 2019), or that are under development, such as the national model for the developed by a consortium led by RSG. In another project for the Federal Highway Administration, a national freight traffic assignment model for the US, also including conversion from 132 Freight Analysis Framework (FAF) zones to OD matrices for 3,500 zones and from tonnes to vehicles, was developed (Rabinovicz and Slavin, 2020).

4. Developments in regional freight transport models

The strategic Flemish freight model (SVRM) is used by the Flemish authorities to forecast the demand for freight transport in the future and to support the decision making process for large infrastructure investments or the implementation of a kilometre charge for heavy goods vehicles (Grebe et al., 2016). The model simulates all national and international flows of goods for road, rail and inland waterway transport for the region of Flanders (northern part of Belgium). It has a classical four-step structure including detailed network models for road rail and inland waterways, with several additions such as a time-period choice model and the choice between direct transport and the use of logistic hubs by mode.

The time-period choice model in the SVRM only applies to road transport (de Jong et al., 2016). It determines the choice of when to carry out the transport, distinguishing seven periods during the day (e.g. the morning and the afternoon peak). It was estimated on SP data collected among receivers of the goods, given that the existing literature had indicated that the receivers are the most important

agents on the period choice in freight transport by setting the delivery time or time window (e.g. Holguin-Veras et al., 2012). This time period model can be used to simulate the impact of changes in the level of congestion on the roads or of kilometre charging schemes with variation in the charges between time periods. Time period choice in road freight transport was also investigated in Australia, using latent curve models, a form of structural equations modelling (Ellison et al., 2015).

The SVRM also distinguishes multiple vehicle types within each mode (three types for road and rail, and six for inland waterways). The calibration took place on aggregate data, due to the absence of disaggregate data on transport flows.

The de Jong et al. (2013) review also mentioned some pioneering freight transport models from North-America (e.g. for Oregon, Calgary, Toronto or the FAME national US model). Since then, North America has been at the forefront of new developments in freight transport modelling.

Florida's FreightSim model (RSG, 2015a) is part of the Florida Statewide Model (FLSWM). It simulates the transport of goods between supplier and buyer (receiver) firms in the US, within, into, out and through Florida. This model also makes the distinction between PC and OD flows. Another similarity with the ADA models is that various components work at the disaggregate level (microsimulation). FreightSim includes a firm synthesis, which synthesises all firms in the US and a sample of international businesses. Then each buyer firm (by type) selects supplier firms in the supplier firm selection module (unlike the ADA approach this step is handled at the disaggregate level, letting the model evolve into a DDA approach). The distribution channels between these firms are modelled as well, e.g., whether a shipment is transported directly or passes through one or more warehouses, intermodal centres, distribution centres, or consolidation centres), as is the choice of shipment size, primary mode (road, rail, air, waterway) and transfer locations. This leads to the determination of trips at the OD level by mode, which for road transport are assigned to the network.

Just as the model for Florida, the freight transport model for the Chicago Metropolitan Agency for Planning (CMAP) uses a firm synthesis, supply chain and logistics microsimulation as well as truck tour formation models (Cambridge Systematics, 2011; RSG, 2015b). The first elements are modelled at the national scale, the latter at the regional scale (the Chicago region).

The national scale portion of the CMAP model focuses on how firms that buy goods select suppliers (DDA) and how suppliers ship goods to their buyers, resulting in PC flows. Multinomial logit choice models determine the supply chain type (direct, 1, 2 or 3+ types of intermediate stops). Furthermore, there are submodels for shipment size, mode and intermediate transfer choice, based on full logistics costs functions as in de Jong and Ben-Akiva (2007). For the supplier selection, for each commodity market, an iterative procurement market game (PMG) is played in which a pool of buyers attempt to procure inputs from a pool of sellers in the market, depending on for instance shipping times, unit costs (transport and non-transport) and risks.

In de Jong et al. (2020) a mode and route choice model for North-East India and Bangladesh is developed and used to answer the question what the transport consequences will be of implementing bilateral and multilateral agreements to facilitate cross-border trade in South Asia. The model is largely based on stated preference (SP) interviews among more than 500 shippers and road haulage firms in northeast India and Bangladesh. The modes included in the model are road, rail inland waterways and coastal shipping, and the model also contains the choice of port (either Kolkata/Haldia in India or Chattogram in Bangladesh).

Holguin-Veras et al. (2020) developed a regional freight model for trucks in Bangladesh using novel methods for building OD matrices for different commodity types. The freight trip distribution for trucks is estimated from secondary data sources, such as traffic counts, GPS data on network travel times and truck payload data, using a technique they call Freight Origin-Destination Synthesis

(FODS). This technique is applied here for the first time in the form of both a single-commodity and a multi-commodity model.

Nugroho et al. (2016) also used SP data, in this case referring to the choice of hinterland mode (road or rail) and port (distinguishing four ports) by exporters and forwarders for exports from Java, Indonesia. The data were analysed using various forms of discrete choice models (multinomial logit, nested logit, mixed logit) and there were applied to study the impact of policies on emissions.

In the PhD thesis of de Tremerie (de Tremerie, 2018), a model is developed for the choice of mode for goods flows going through the port of Ghent in Belgium. The models were estimated on withinmode and between-mode (road, rail, inland waterways, short-sea shipping) SP experiments with shippers in the port area. The attributes include also the CO₂ emissions of the transport. The estimated models are the multinomial logit and mixed logit model, but hybrid models (ICLV models) have been estimated as well, using additional information collected in the survey on the level of agreement of the shippers with statements about making transport greener. On the basis of this information, latent variables were identified for the attitude of the firm and/or the individual respondent towards the environment, that helped explain the choice between modes.

Tapia et al. (2020) similarly did an SP on mode (road versus rail) and port choice (unlabelled port alternatives), in this case for specific agricultural products in Argentina. In this paper, not only discrete choice models were estimated but also multiple discrete-continuous extreme value (MDCEV) models (MDCEV). These latter models were appropriate, because the choice experiments asked for the percentage allocated to each alternative instead of a single discrete choice. There were also joint SP/RP models with disaggregate consignment bill data.

5. Developments in urban freight transport models

In order to support urban planners to optimise city logistic solutions, urban freight transport models are gaining interest.

In The Netherlands, a new urban multi-agent simulation model was developed, called MASS-GT (de Bok and Tavasszy, 2018), that was adopted in the EU H2020 HARMONY modelling framework as a tactical freight simulator. It is agent- and shipment-based and uses a novel high-density data collection of truck trip diaries as empirical basis. Logistic choices are simulated using discrete choice models, such as the formation of trips into multiple-drop tours (Thoen et al., 2020a) or simultaneous vehicle and shipment size choice (Mohammed et al., 2019). The scope of the model is urban freight transport demand and the modelling focusses on road transport.

The tour formation model is a random utility model, estimated on disaggregate data for over 2 mln shipments, that is gathered automatically from the planning systems of carriers transporting goods in the Netherlands by road. This choice model is embedded in an algorithm that works iteratively by incrementally allocating each shipment to a specific tour, taking account of differences between commodity types, vehicles and types of locations (Thoen et al., 2020a).

The model can be applied for the impact assessment of urban logistics policies, such as zero-emission zoning schemes (de Bok et al., 2020), and calculate numerous Key Performance Indicators, such a vehicle kilometres and emissions (Thoen et al., 2020b). The level of detail in the multi-agent model also permits the implementation of detailed urban freight scenarios, and makes it possible to better account for heterogeneity in responses of different actors in city logistics. International, and interregional freight demand patterns at NUTS 3 level are input to the simulator and can be derived from strategic models such as BasGoed for The Netherlands, or HighTool, TransTools or TriMode at

an European scale. This top-down approach allows the integration of modal split, or shifts in interregional trade patterns into the regional simulation. The current implementation of this model is for the Province of Zuid-Holland in the Netherlands.

SimMobility Freight is another example of a recent urban freight simulator (Alho et al., 2017, Sakai et al., 2020). It is developed as part of SimMobility, a multi-scale agent-based urban transport simulation platform. SimMobility Freight is capable of simulating commodity contracts between firms (encompassing supplier choice), inventory and transport logistics and vehicle operation planning and parking decisions in a fully disaggregate manner. Logistic decision making is simulated on three distinct temporal dimensions: long-term (freight generation, supplier selection, shipment size), mid-term (transport logistics and vehicle planning) and short-term (dynamic traffic assignment). It simulates the behaviour of individual agents, using discrete choice models based in part on vehicle tracking and establishment data. It has been implemented in Singapore.

In the mid-term component of SimMobility Freight, freight activity schedules are generated for each vehicle in the fleet of the carriers. It handles the conversion of shipment demand (in terms of a list of commodity contracts between senders and receivers) to vehicle tours. This step includes the selection of time-window and of carrier and shipment-to-vehicle allocation and tour formation for an average day. The output consists of vehicle operations plans with information on stop locations, arrival, and departure times, and stop purposes (overnight parking, pickup or delivery). These plans, essentially outlining vehicle tours, are then used in the mesoscopic or microscopic traffic simulations.

Currently, work is underway to include firm strategy as a determinant of vehicle fleet decisions, for which latent class discrete choice models are estimated using a novel data analysis methodology on existing firm strategy documents instead of carrying out new surveys that often attain a low response rate (Stinson and Mohammadian, 2020). This research project has also studied the possibility of moving parcels in passenger vehicles (in this case for autonomous mobility-on-demand vehicles; Alho, 2020), in this way also further integrating passenger and freight transport modelling.

The POLARIS model is a forecasting tool that can be applied at different spatial levels (from a small neighbourhood up to the regional scale of a metropolitan area) and for different areas. It was developed by the U.S. Department of Energy's Argonne National Laboratory. The freight model that was recently integrated into the POLARIS platform simulates the decisions that businesses and other agents make at the micro-level, just as do some of the regional models in the US discussed above (such as Florida's FreightSim). It includes the formation of the supply chain. For this, POLARIS distinguishes between push and pull supply chains: in push environments, manufacturing is driven from the producer down to the retailer based on forecasts of demand; in pull environments it is driven by information on consumer demand. POLARIS captures push-pull dynamics by establishing information links to represent which producers have information about demand and which do not. In this way, it can predict demand for last-mile just-in-time deliveries (Stinson, 2020a). This framework can be used to compare traditional shopping trips against commercial vehicle e-commerce delivery trips (Stinson, 2020b), also because it includes both passenger and freight transport.

Nuzzolo et al. (2014) developed a simulation model for urban freight transport in Rome, Italy. This model consists of three main parts. First, the commodity flows between zones are determined per transport type (retailer own-account, retailer third-party, wholesaler own-account, wholesaler third-party). Second, the commodity flows are divided into discrete shipments based on an average shipment size and each shipment is assigned a delivery time period based on a discrete choice model. Third, the shipments are assigned to vehicles using a discrete choice-based algorithm for tour formation (Nuzzolo et al., 2012). While not as agent-focused as MASS-GT and SimMobility Freight, this model provides another good example of more disaggregate shipment-based modelling of urban freight

transport. The issue of the timing of the last-mile delivery under delivery time windows is also studied in Pahwa and Jaller (2020).

The TRABAM model for Flanders, Belgium, focusses on the decisions made by carriers (Mommens et al., 2017). A freight generation model determines the zonal productions and attractions, which are divided into individual shipments based on the Economic Order Quantity formula, as is done by Ben-Akiva and De Jong (2013). Each shipment is assigned to a carrier based on the size and the location of the carrier's depots. These carriers optimise a set of tours to transport all the shipments. The set of carriers in the model is based on rich data on Belgian third-party carriers and their vehicle fleet and depots. One innovative aspect of this modelling framework is the inclusion of 'learning' by the carrier agents. If the success rate of delivery of shipments is considered too low, the carriers can react to this by, for example, expanding their vehicle fleet. Finally, the model also includes an emission calculation which considers the diffusion of pollutant gasses, which leads to a better estimation of the local exposure to these gasses (Mommens et al., 2019).

The above-mentioned urban modelling frameworks show a clear development towards more disaggregate modelling of urban freight transport through shipment-based and agent-based features. Another development we can identify is an increased effort to include transport resulting from e-commerce in urban freight models. MASS-GT (Thoen et al., 2020b), TRABAM (Mommens et al., 2020), POLARIS and SVRM (Grebe et al., 2016), for example, were all expanded with a module for parcel deliveries in recent years. Llorca & Moeckel (2020) use the FOCA model of Munich to simulate the effects of different shares of cargo bikes and densities of local micro depots. Le Pira et al. (2020) analyse e-groceries and consumers' preferences for home deliveries vs. store pick-up.

Recent literature also shows a vast body of research on applying dynamic agent-based models in the urban freight context (Roorda et al., 2010; Marcucci et al., 2017; Anand et al., 2019). These models study dynamic behaviour between and within agents (negotiation, learning) and are behaviourally more realistic and complex than the standard city logistics models. This complexity however causes great challenges for the calibration of these models, due to absence of data for such strategic decision making, and the computational burden involved with the simulated behaviour.

6. Looking back at the expected developments

Since the start of this century, there has been a tendency to include more logistics aspects in freight transport modelling. This tendency, that already manifested itself before 2013, has continued in the past seven years: many new models at the international, national and regional level distinguish between PC and OD flows and explain the multimodal transport chain for the PC flow (HIGH-TOOL, Transtools3, TRIMODE, Basgoed container model, new ADA models, FreightSim, CMAP model). Some of these models also distinguish the choice of intermediate storage location along the distribution channel (e.g. TRIMODE, FreightSim). For urban freight transport, multimodality is usually of less importance, road transport until very recently often being the only game in town, but there is a tendency to include more logistics aspects at this level as well (e.g. shipment size, tour formation).

There has also been considerable progress since 2013 on most of the expected additional areas for developments from the list in de Jong et al. (2013):

- Modelling of further logistics decisions, especially supply chain formation. This is included in FreightSim, the CMAP model, POLARIS and SimMobility Freight.
- Integration of (inter)national (intercity) freight models with urban freight models. The CMAP model, POLARIS and MASS-GT are examples of this.

- Integration of freight transport models with passenger transport models. POLARIS goes some way in this respect (dependence of freight flows on consumer demand) and so does SimMobility (e.g. crowd-sourcing of parcel deliveries); The importance of this integration, given the increasing importance of online ordering and home deliveries replacing conventional shopping trips, is widely acknowledged.
- Including latent variables (e.g. on attitudes) in freight transport models leading to hybrid models with hard (e.g. time and cost) and soft (e.g. attitude towards the environment) variables.

Several discrete choice models based on SP data use transport time reliability or the probability of damage or theft (e.g. Konstantinus et al., 2020; de Jong et al., 2020; Tapia et al., 2020). Latent variables in the ICLV framework are used in Konstantinus (2019), de Tremerie (2018) and Stinson and Mohammadian (2020). The general popularity of the ICLV model has decreased since Vij and Walker (2016) warned that this model might have difficulty in properly identifying the latent variable coefficients from other influences on choice. Another issue with these models is the difficulty of predicting the future values of the attitudinal variables.

The other expected developments from de Jong et al. (2013) have not taken off in a major way:

- Integration of production, inventory and transport logistics.

POLARIS goes somewhere in this direction (demand-led versus top-down supply chains), but further than that we are not aware of attempts to model production decisions jointly with transport and inventory logistics decisions in forecasting and policy evaluation models for the public sector.

- Departure (or rather delivery) time modelling.

As far as we are aware, this has not been taken up in any international or national freight transport model. This is not so surprising, since much transport in these models are multiday, and the precise timing of the delivery on the delivery day in this context is difficult and highly uncertain. The only regional freight transport model we know of with a component for time period choice is SVRM, the model for Flanders (and then only for the road mode). In the urban context there might be more scope for delivery time modelling. Time period is an endogenous variable in the model of Nuzzolo et al. (2014), in SimMobility Freight and it was studied by Pahwa and Jaller (2020). A time period choice submodel seems most relevant in congested urban areas and in situations where the authorities are considering truck charges with variation by time-of-day.

7. Other developments since 2013

Notwithstanding the progress that has been made in recent years in regional to international freight transport models, the area where most progress had been made since 2013 seems to be urban freight transport modelling. This development has at least partly been driven by policy-relevant issues that are especially important at the urban level, such as harmful emissions, congestion, limited parking space, growth of e-commerce and direct deliveries to consumers and the (possible) introduction of new modes of freight transport, such as cargo-bikes, drones, crowdsourcing of parcel deliveries and automated vehicles.

The recent development in urban freight transport models include:

- More modelling at the level of shipments: microsimulation (to a lesser degree this development is also taking pace at regional and national level, e.g. in the ADA models);

- Explicit consideration of carriers, sending firms, receiving firms (to a lesser degree this is also taking place at the regional level, such as the Florida's FreightSim model);
- Dynamic agent-based aspects: negotiation of contracts, learning (also at the regional level: Florida's FreightSim and the CMAP model);
- Explicit consideration of tour formation;
- Specific models for parcel deliveries;
- More detailed emission calculations.

These are developments that were not included in the list of expected developments in de Jong et al. (2013). This is partly due to the fact that the 2013 paper focussed on regional to international models, not on the urban case. Modelling the formation of multi-sender and/or multi-receiver tours for example had already started before 2013 (e.g. Wang and Holguin-Veras, 2009), but was considered too detailed and computer-intensive for (inter)national and regional models in 2013. Most new developments on tour formation have indeed taken place at the urban level, but it is now also done at the regional model (in the CMAP model).

A development that was not on the list of 2013 and that is not specific for urban models is the use of other model specifications than standard regression and the discrete choice model (such as the joint discrete-continuous model, including MDCEV, see Tapia et al., 2020), though as before this is an adaptation from passenger transport modelling. Another unlisted development is the explicit modelling of port choice as a separate step in the freight transport model, especially on SP data (Nugroho et al., 2017; Tapia et al., 2020; de Jong et al., 2020).

8. Summary, conclusions and future outlook

In the Biblical story, the seven fat years in Egypt were followed by seven lean years. Freight transport modelling has long been a field where only a limited amount of research took place, and the research that was done largely borrowed its key concepts from passenger transport modelling. More or less since the beginning of this century, freight transport modelling has been receiving more attention and has seen more original development, notably the inclusion of more logistics concepts into the models.

In 2013, freight transport modelling had already seen two periods of around seven years that can be regarded as fat. Our conclusion from the review above is that the period 2013-2020 can be regarded as seven fat years as well. In a longer time perspective, the lean decades before 2000 have been followed by series of two decades of fat years for freight transport modelling.

We see every reason to assume that these fat years will continue in the coming decade. Especially at the urban level (see section 7), many problems but also many potential solutions exist that are related to freight transport. New developments in passenger transport modelling may be relevant for freight as well, such as discrete-continuous models and latent variable models in the recent past and maybe models with endogenous choice sets and explicitly dynamic models in the near future.

We expect that the general tendency towards more shipment-level micro-simulation models will continue, in spite of the difficulty of obtaining disaggregate data, and that this will also go for the shift towards agent-based models with several interacting agents and the possibility of learning behaviour. Also we expect that the expansion of choices modelled (from generation, distribution, mode and route choice towards: supplier and receiver, distribution channel, shipment size, port, consolidation and distribution, fleet size and composition choice as well as tour formation, including failed deliveries, returning ordered goods and empty vehicle trips) is here to stay and become more mature. Further integration with production choices does not seem to be high on the research agenda, and maybe this

also goes for time period choice in freight transport. The integration of freight models at different spatial levels and of freight and passenger transport models is also very likely to continue.

References

- Abate, M., I. Vierth, G.C. de Jong and J. Baak (2014) Joint econometric models of freight transport chain and shipment size choice, CTS working paper 2014:9
- Abate, M., I. Vierth, R. Karlsson, G.C. de Jong and J. Baak (2018), A disaggregate stochastic freight transport model for Sweden, *Transportation*, <https://doi.org/10.1007/s1116-018-9856-9>.
- Alho, A., Bhavathrathan, B., Stinson, M., Gopalakrishnan, R., Le, D.-T., & Ben-Akiva, M. (2017). A multi-scale agent-based modelling framework for urban freight distribution. *Transportation Research Procedia* 27, 188-196.
- Alho, A. (2020) Tapping into autonomous mobility-on-demand spare capacity to move parcels. How much freight can be moved? Are passengers affected? Paper presented at TRB 2020, Washington DC..
- Anand, N., R. van Duin and L. Tavasszy (2019) Carbon credits and urban freight consolidation: An experiment using agent based simulation. *Research in Transportation Economics*, DOI: 10.1016/j.retrec.2019.100797.
- Baumol, W.J. and H.D. Vinod (1970) An inventory-theoretic model of freight transport demand. *Management Science*, 16, 413-421.
- Bayliss, B.T. and S.L. Edwards (1970) *Industrial demand for transport*, HMSO, London.
- Bayliss, B.T. (1988) *The measurement of supply and demand in freight transport*, Avebury, Aldershot, U.K..
- Ben-Akiva, M.E. and G.C. de Jong (2013) The aggregate-disaggregate-aggregate (ADA) freight model system, in *Freight Transport Modelling* (Eds.: M.E. Ben-Akiva, H. Meersman and E. van de Voorde), Emerald.
- Bok, M. de, G.C. de Jong, L. Tavasszy, J. van Meijeren, I. Davydenko, M. Benjamins, N. Groot, O. Miete and M. van den Berg (2018) A multimodal transport chain choice model for container transport, *Transportation Research Procedia* 31, 99-107, 2018.
- Bok, M. de and L. Tavasszy (2018) An empirical agent-based simulation system for urban goods transport (MASS-GT), *Procedia Computer Science* 130: 8.
- Bok, M. de, L. Tavasszy and S. Thoen (2020) Application of an empirical multi-agent model for urban goods transport to analyze impacts of zero emission zones in The Netherlands, *Transport Policy* <https://doi.org/10.1016/j.tranpol.2020.07.010>.
- Cambridge Systematics (2011) *A Working demonstration of a mesoscale freight model for the Chicago Region, Final Report and User's Guide prepared for the Chicago Metropolitan Agency for Planning*.
- Chiang, Y., P.O. Roberts and M.E. Ben-Akiva (1981) *Development of a policy sensitive model for forecasting freight demand. Final report, Center for Transportation Studies Report 81-1, MIT, Cambridge, Massachusetts*.
- Ellison, R.B., S.P. Greaves and D.A. Hensher (2015) *Assessing dynamic responses of freight operators to government policies: a latent curve modelling approach*, paper presented at IATBR 2015, Windsor.

- Grebe S, G.C. de Jong, M. de Bok, P. van Houwe and D. Borremans (2016) The strategic Flemish freight model at the intersection of policy issues and the available data, Paper presented at the European Transport Conference 2016, Barcelona
- Grebe, S., G.C. de Jong, C. Wampera, C. Obermayer and R. Pompl (2020) VMÖ – A new strategic transport model for Austria, Special ETC 2019 issue of Transportation Research PROcedia (TR-PRO), 49, 95-106.
- Halim, R. (2017) Strategic modeling of global container transport networks, PhD thesis, Delft University of Technology.
- Holguín-Veras, J., K. Ozbay, A. Kornhauser, S. Ukkusuri, M. Brom, S. Iyer, W. Yushimito, B. Allen and M. Silas (2012) Overall impacts of off-hour delivery programs in the New York City Metropolitan Area: Lessons for European cities, Paper presented at European Transport Conference 2012, Glasgow
- Holguín-Veras, J., C. Wang, L. K. Kalahasthi, S. Campbell, M. Lawrence, J. Skolnik, I. Silvergleit, C. A. Gonzalez-Calderon, J. Wojtowicz, D. Ramirez-Rios, M. Arrieta-Prieto, O. Calderon-Quevedo and S. Perez-Guzman (2019) Impacts of Policy-Induced Freight Modal Shifts, NCHRP/NCFRP. Washington, D.C., Transportation Research Board. NCFRP Report 40.
- Holguin-Veras, J., L. Kalahasthi, A. Ismael, N. Yushimito, M. Herrera Dappe and S. Hogue (2020) Regional freight demand model for Bangladesh: an application of freight OD synthesis, Paper presented at TRB 2020, Washington, DC.
- ITF (2019) ITF Transport Outlook 2019, ITF/OECD, Paris.
- Jensen, A.F., M. Thorhauge, G.C. de Jong, J. Rich, T. Dekker, D. Johnson, M. Ojeda Cabral, J. Bates and O. Anker Nielsen (2019) A disaggregate freight transport chain choice model for Europe, Transportation Research E, 121, 43-62, 2, <https://doi.org/10.1016/j.tre.2018.10.004>.
- Jong, G.C. de and M.E. Ben-Akiva (2007) A micro-simulation model of shipment size and transport chain choice, Special issue on freight transport of Transportation Research B, 41, pp. 950-965.
- Jong, G.C. de, A. Burgess, L. Tavasszy, R. Versteegh, M. de Bok and N. Schmorak (2011) Distribution and modal split models for freight transport in The Netherlands, Paper presented at the European Transport Conference 2011, Glasgow.
- Jong, G.C. de, I. Vierth, L. Tavasszy and M.E. Ben-Akiva (2013) Recent developments in national and international freight transport models within Europe, Transportation, Vol. 40-2, pp. 347-371.
- Jong, G.C. de, M. Kouwenhoven, K. Ruijs, P. van Houwe and D. Borremans (2016) A time-period choice model for road freight transport in Flanders based on stated preference data, Transportation Research E, February 2016, pp. 20-31.
- Jong, G.C. de, R. Tanner, J. Rich, M. Thorhauge, O.A. Nielsen and J. Bates (2017) Modelling production-consumption flows of goods in Europe: the trade model within Transtools3, Journal of Shipping and Trade, 2017, 2:5, <https://doi.org/10.1186/s41072-017-0023-9>.
- Jong, G.C. de, M. Sharma, M. Kouwenhoven, G. van Eck, Y. Araghi, R. Mittal, M. Pratap, M. Herrera Dappe and M. Abate (2020) Analysis of route and mode transport choice in eastern south asia following integration agreements, in: Herrera Dappe, M. and C. Kunaka (Eds.), Connecting to Thrive: Challenges and Opportunities of Transport Integration in Eastern South Asia. International Development in Focus, Washington, DC: World Bank.

- Konstantinus, A. (2019) Opportunities for short-sea shipping in SADC: Evidence based on discrete choice modeling, Ph.D. Dissertation, Department of Civil Engineering, University of Cape Town, Cape Town, South Africa (2019)
- Konstantinus, A., M. Zuidgeest, S. Hess and G.C. de Jong (2020) Assessing Inter-Urban Freight Mode Choice Preference for Short-sea Shipping in the Southern African Development Community Region, *Journal of Transport Geography*, 2020.
- Le Pira, M., Marcucci, E., Gatta, V., Pluchino, A., Martina, F., Inturri, G. (2020). Simulating urban freight flows in e-grocery scenarios accounting for consumer heterogeneous preferences. Paper presented at IEEE 2020, Delft, the Netherlands.
- Lindgren, S., M. Johansson, I. Vierth, R. Karlsson, J. Baak and G.C. de Jong (2019) Estimation and evaluation of discrete choice models, VTI, Stockholm.
- Llora, C., Moeckel, R. (2020). Study of Cargo Bikes for Parcel Deliveries under Different Supply, Demand and Spatial Conditions. Paper presented at IEEE 2020, Delft, the Netherlands.
- Marcucci, E., M. Le Pira, V. Gatta, G. Inturri, M. Ignaccolo and A. Pluchino (2017) Simulating participatory urban freight transport policy-making: Accounting for heterogeneous stakeholders' preferences and interaction effects, *Transportation Research Part E: Logistics and Transportation Review*, 103: 69-86.
- Martino, A, I. Williams, D. Fiorello, K. Noekel, P. Capros, P. Siskos, G. Zazias, I. Charalampidis, P. Karkatsoulis and W. Schade (2018) TRIMODE – integrated transport model for Europe, *Proceedings of 7th Transport Research Arena TRA 2018*, April 16-19, 2018, Vienna, Austria.
- Mohammed, R.A., I. Bal, M. de Bok and L. Tavasszy (2019) A disaggregate behavioral model for joint shipment size and vehicle type logistic choice decision, Paper presented at the 8th hEART Symposium, September 4-6, Budapest, Hungary.
- Mommens, K., T. van Lier, C. Macharis (2016). Belgian carriers as agent in a national agent-based freight transport model. 14th world conference on transport research, Shanghai, China.
- Mommens, K., N. Brusselaers, T. van Lier, C. Macharis (2019). A dynamic approach to measure the impact of freight transport on air quality in cities. *Journal of Cleaner Production* 240, 118192.
- Mommens, K., Rai, H.B., van Lier, T., Macharis, C. (2020). Homedeliveries or delivery to collection points? An environmental impact analysis for urban, urbanized and rural areas in Belgium. Paper presented at IEEE 2020, Delft, the Netherlands.
- Nugroho, M., G.C. de Jong and A.E. Whiteing (2016) Port and inland mode choice from the exporters' and forwarders' perspectives: Case study - Java, Indonesia, *Research in Transportation Business and Management*, 10.1016/j.rtbm.2016.03.010
- Pahwa, A. and M. Jaller (2020) Evaluating the costs and distribution structure in last-mile deliveries under short time windows, Paper presented at TRB 2020, Washington, DC.
- Rabinovicz, S, and H. Slavin (2020) A new tool for nationwide freight traffic assignment, paper presented at European Transport Conference 2020 (online).
- RSG (2015a) FreightSIM, <https://rsginc.atlassian.net/wiki/display/FREIGHTSIM/FreightSim>.
- RSG (2015b) User's guide and model documentation: agent-based supply chain modeling tool, Chicago: Chicago Metropolitan Agency for Planning.

- Roorda, M. J., R. Cavalcante, R. S. McCabe, H. Kwan (2010), A conceptual framework for agent-based modelling of logistics services." *Transportation Research Part E: Logistics and Transportation Review*, 46(1): 18-31.
- Sakai, T., A. Alhoa, B. Bhavathrathan, G. Chiara, R. Gopalakrishnan, P. Jing, T. Hyodo, L. Cheah and M. Ben-Akiva (2020) SimMobility Freight: An Agent-Based Urban Freight Simulator for Evaluating Logistics Solutions, *Transportation Research Part E Logistics and Transportation Review*, 141 DOI: 10.1016/j.tre.2020.102017.
- Samimi, A., A. Mohammadian and K. Kawamura, K. (2010) A behavioral freight movement microsimulation model: method and data, *Transportation Letters: The International Journal of Transportation Research*, 2010: Volume 2, 53-62.
- Stinson, M. and A. Mohammadian (2020) Modeling Firm Transportation Strategy Using Big Text Data. Paper presented at IEEE 2020, Delft, the Netherlands.
- Stinson, M. (2020a) New tool simulating freight movement quantifies impacts of e-commerce and tech on transportation, www.anl.gov.
- Stinson, M. (2020b) Citywide impacts of e-commerce: does parcel deliveries travel outweigh household shopping travel reductions? Presentation at TRB 2020, Washington DC.
- Szimba, E., J. Ihrig, M. Kraft, M. Mitusch, M. Chen, M. Chahim, J. van Meijeren, J. Kiel, B. Mandel, A. Ulied, E. Larrea, G. de Ceuster, R. van Grol, Z. Berki, A. Szekely and R. Smith (2018) HIGH-TOOL – a strategic assessment tool for evaluating EU transport policies, *Journal of Shipping and Trade*, 3, 11 (2018), <https://doi.org/10.1186/s41072-018-0037-y>.
- Tapia, R.J., G.C. de Jong, A.M. Larranaga and H.B. Cybis (2020) Application of MDCEV to infrastructure planning in freight transport, *Transportation Research A*, 133, 255-271.
- Toen, S, L. Tavasszy, M. de Bok, G. Correia and R. van Duin (2020a) Descriptive modeling of freight tour formation: A shipment-based approach, *Transportation Research Part E: Logistics and Transportation Review*, 140. <https://doi.org/10.1016/j.tre.2020.101989>.
- Toen S, M. de Bok, L. Tavasszy (2020b) Shipment-Based Urban Freight Emission Calculation. Paper presented at IEEE 2020, Delft, the Netherlands.
- Tremerie, L.M.F. (2018) An application of quantitative and qualitative methods in freight mode choice modelling, PhD thesis, Institute for Transport Studies, University of Leeds.
- TRT (2018) Description of the TRUST model, TRT Trasporti e Territorio, Milan.
- Vij, A. and J. Walker (2016) How, when and why integrated choice and latent variable models are latently useful, *Transportation Research Part B: Methodological*, 90, , 192-217, DOI - 10.1016/j.trb.2016.04.021
- Wang, Q. and J. Holguin-Veras (2009) Tour-based entropy maximization formulations of urban freight demand, Paper presented at the 88th Annual Transportation Research Board Conference, TRB, Washington.
- Wesseling, B, M. de Bok, J. Spruijt, O. Usman and T. van Bree (2020) Energy transition scenarios in the strategic freight model BasGoed, Paper presented at the European Transport Conference 2020 (online).
- Winston, C. (1981) A disaggregate model of the demand for intercity freight transportation, *Econometrica*, Vol.49, No. 4, 981-1006.